

# Epson TM-T88IV Series

DATASHEET / BROCHURE



Devote more time to customer service by trusting your point of service to this world leading thermal receipt printer

Epson TM-T88IV

## Enhanced customer service

Designed specifically for high-volume sales environments, the thermal TM-T88IV offers 25% faster printing than its predecessor, a redesigned case, two-colour capability and new easy-to-use features. With its 200mm per second print speed, enhanced graphic capability and increased user memory, the TM-T88IV delivers ultra-fast results. Unlike other printers, it prints text, barcodes and graphics at the same fast speed to deliver intelligent receipts with customer impact whilst helping to increase transaction speed.

## Easy-to-use

The TM-T88IV features easy drop-in paper roll loading, autocutter, full auto status back reporting, enhanced cable management system, optional external power supply mounting, maintenance counter and optional buzzer.

## Compact, robust and reliable

This printer's small footprint and re-designed case makes it ideal for all demanding retail and hospitality environments. It can also be wall mounted using an optional bracket to further save space. The TM-T88IV benefits from lower power consumption and offers increased reliability with a MCBF of 52 million lines, a MTBF of 360,000 hours and an autocutter life of 1.5 million cuts.

## Versatile and adaptable

The TM-T88IV includes a range of high-speed interfaces such as USB 2 and Powered USB, Ethernet, serial and parallel. It also includes new OPoS, Java and Win APD drivers for seamless integration with existing systems.

## KEY FEATURES

## PRODUCT SPECIFICATIONS

<b>PAPER</b>	
Paper size	79.50 ± 0.50 (W) mm x dia 83.00 mm, 575.00 ± 5.00 (W) mm x dia 83.00 mm (option)

<b>INTERFACES</b>	
Interfaces	RS-232, Drawer kick-out

<b>POWER</b>	
Power Supply	PS-180 (option)
Power Consumption	standby: 0.1 A, Mean: 1.8 A
Operating voltage	24 V

<b>GENERAL</b>	
Product dimensions	145 x 195 x 148 mm (Width x Depth x Height)
Product weight	1.8 kg
Colour	Epson Dark Grey / Epson Cool White
Noise Level	Operation: 55 dB (A)
Installation	horizontally, vertically with wall hanging bracket
Interface connectors	D.K.D. function (2 drivers)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -10° C - 50° C

<b> FONTS &amp; STYLES</b>	
Print Speed	200 mm/sec
Character size	0.99 mm (W) x 2.4 mm (H) / 1.41 mm (W) x 3.39 mm (H)
Character set	95 Alphanumeric, 48 International, 128 x 11 Graphic
Characters per inch	20 cpi / 15 cpi
Dot density	180 dpi x 180 dpi

<b>STANDARDS COMPLIANCE</b>	
EMC Standards	CE marking
Safety standards	TÜV

<b>OTHER FEATURES</b>	
Changeable interface	Yes

## Epson TM-T88IV Series

### WHAT'S IN THE BOX

- Main unit
- User manual
- Power switch cover
- Connector Cover

### OPTIONAL ACCESSORIES

- WH-10 (040) Wall hanging bracket  
C32C845040
- PS-180: Universal Power Supply  
C32C825341
- Epson UB-P02II  
C32C823891
- UB-S01  
C32C823361
- UB-S09  
C32C823861
- UB-U02III  
C32C824121
- UB-U03II  
C32C824131
- UB-U05  
C32C823991
- UB-U06  
C32C824071

Co<sup>✓</sup>erPlus

Epson Middle East  
P.O.Box 17383, Dubai  
United Arab Emirates  
Telephone: +9714 8818934

Hotline Telephone: +9714 8872172  
Fax: +9714 8818945  
E-mail: supportme@epson.co.uk  
www.epson.ae

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.  
Product information is subject to change without prior notice.

**EPSON**®