

PRODUCT SPECIFICATIONS

PAPER	
Paper size	76.00 ± 0.50 (W) mm x dia 83.00 mm, 69.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm
Copy capability	one copies plus one original

INTERFACES	
Interfaces	RS-232, Drawer kick-out, Bidirectional parallel

POWER	
Power Supply	PS-180 (option)
Operating voltage	24 V

GENERAL	
Product dimensions	160 x 248 x 139 mm (Width x Depth x Height)
Product weight	2.7 kg
Colour	Epson Dark Grey / Epson Cool White
Noise Level	Operation: 64 dB (A)
Installation	horizontally, vertically with wall hanging bracket
Interface connectors	D.K.D. function (2 drivers)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Storage -10° C - 50° C

FONTS & STYLES	
Print Speed	4.70 lps (40 columns, 16.00 cpi)
Character size	1.6 mm (W) x 3.1 mm (H) / 1.2 mm (W) x 3.1 mm (H)
Character set	95 Alphanumeric, 48 International, 128 x 12 Graphic
Characters per inch	13.3 cpi / 16 cpi

STANDARDS COMPLIANCE	
EMC Standards	CE marking
Safety standards	TÜV

OTHER FEATURES	
Changeable interface	Yes
Cutter	Partial Cut

Epson TM-U220A Series

WHAT'S IN THE BOX

- Main unit
- User manual
- Ribbon
- Thermal roll paper
- Roll paper
- PS-180

SUPPLIES

- Epson ERC38B Ribbon Cartridge for TM-U200/U210/U220/U230/U300/U375, black (C43S015374)
- Epson ERC38BR Ribbon Cartridge for TM-300/U300/U210D/U220/U230, black/red (C43S015376)

OPTIONAL ACCESSORIES

- WH-10 (040) Wall hanging bracket
C32C845040
- PS-180: Universal Power Supply
C32C825341
- Epson UB-P02II
C32C823891
- UB-S01
C32C823361
- UB-S09
C32C823861
- UB-U02III
C32C824121
- UB-U03II
C32C824131
- UB-E04: 10/100 BaseT Ethernet I/F Board
C32C881008

Co[✓]erPlus

Epson Middle East
P.O.Box 17383, Dubai
United Arab Emirates
Telephone: +9714 8818934

Hotline Telephone: +9714 8872172
Fax: +9714 8818945
E-mail: supportme@epson.co.uk
www.epson.ae

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®