

# TM-P80 with Bluetooth

## DATASHEET



Are you a hospitality business looking to reduce queues and increase positive customer feedback? If so, this device is the ideal choice. With Bluetooth connectivity, this thermal receipt printer is great for outdoor use. The TM-P80 can also handle printing barcodes and 2D symbols, making this reliable device a must-have product for hospitality.

### Easy-to-use

If you need to print 80mm-wide receipts, this efficient thermal POS printer is ideal, and it has a convenient belt clip for mobile use.

The TM-P80 features an Auto Paper Reduction Function, that automatically reduces the receipt margin and length by up to 23 percent, all without altering the data or print speed.

### Efficient

With printing speed up to 100mm/sec and a long battery life, queues and delays while paying are greatly reduced. The battery lasts up to 40 hours in Bluetooth mode, making it long-lasting and reliable.

### Reliable

This robust model has Bluetooth connectivity, which is ideal if you will be using the printer outside, as it doesn't require a network.

The portable printer is rugged and resistant to small knocks and drops. Its Mean Time Before Failure is 120,000 hours and its Mean Cuts Before Failure is 16,000,000 lines.

## KEY FEATURES

- **Convenience**  
Bluetooth connectivity, portable receipt printing
- **High-performance**  
Prints receipts at up to 100mm/sec.
- **Reliability**  
Compact and robust design
- **Epson ePOS-Print**  
XML command compatible
- **Easy integration**  
No drivers to install or update

## PRODUCT SPECIFICATIONS

<strong>INTERFACES</strong>	
Interfaces	USB 2.0 Type Mini-B, Bluetooth
<strong>POWER</strong>	
Power Supply	PS-11
Battery Life	Bluetooth 46 Hours
<strong>GENERAL</strong>	
Product dimensions	110 x 140 x 64 mm (Width x Depth x Height)
Product weight	0.5 kg
Colour	Black (EBCK)
Noise Level	Operation: 53 dB (A)
Installation	horizontally, vertically
Humidity	Operation 10% - 90%
Temperature	Storage -25° C - 70° C
<strong>FONTS &amp; STYLES</strong>	
Print Speed	100 mm/sec
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
Dot density	203 dpi x 203 dpi
Printing Characters	Text (incl. Euro symbol), Graphics, Barcode
<strong>DATA BUFFER</strong>	
Data Buffer	4,096 Bytes
<strong>STANDARDS COMPLIANCE</strong>	
EMC Standards	FCC class A, CE marking
Safety standards	UL, CSA
<strong>OTHER</strong>	
Warranty	12 months Carry in Optional warranty extension available

## LOGISTICS INFORMATION

SKU	C31CD70521
EAN code	8715946542324
Dimensions Single Carton	400 x 333 x 259 mm
Carton Weight	5.5 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	216 Units
Pallet Size Block	432 Units

## TM-P80 with Bluetooth

### WHAT'S IN THE BOX

- Battery (OY-BY60II)
- Belt clip
- Main unit
- Roll paper
- USB cable

### OPTIONAL ACCESSORIES

- OT-BY60II: Lithium-ion battery for TM-P60II/P80 C32C831091
- OT-CH60II: Multi battery charger for TM-P60II/P80 C32C825374
- PS-11: Power supply for TM-P60II/P80 C32C825375
- OT-SB60II: Single battery charger for TM-P60II/P80 C32C881007



CoverPlus

For more information please contact:

Telephone: 01952 607111 (UK)+  
01 436 7742 (Republic of Ireland)  
E-mail: [enquiries@epson.co.uk](mailto:enquiries@epson.co.uk)  
Chat: [etalk.epson-europe.com](https://etalk.epson-europe.com)  
Fax: 0871 222 6740  
+ Local call rate.

Web: [www.epson.co.uk](http://www.epson.co.uk)  
[www.epson.ie](http://www.epson.ie)

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.  
Product information is subject to change without prior notice.

**EPSON®**